

Intended purpose

Universal stoppers series 260

For external threads and bolts

Item number	For external threads Size DIN 13	For external threads Size DIN 2999	For Smooth bolts of Ø ... to Ø ...
260 095		M 8	6,8 – 8,2
260 125	R 1/8"	M 10	9,5 - 11,2
260 140		M 12	11,4 – 12,6
260 155	R 1 1/4"		12,2 – 13,6
260 160		M 14	13,2 – 14,6
260 185	R 3/8"		15,6 – 17,3
260 190	R 1/4"		12,6 – 15,0
260 200		M 18	17,0 – 19,0
260 205	R 3/8"		14,2 – 17,5
260 210		M 20	18,4 – 20,0
260 225	R 1/2"		20,1 – 21,5
260 245		M 22	21,2 – 23,0
260 285	R 3/4"		25,6 – 27,2
260 310		M 30	28,2 – 30,0
260 350	R 1"	M 34	31,8 – 34,0
260 375		M 36	34,2 – 36,5
260 400		M 38	36,8 – 39,0
260 440	R 1 1/4"	M 42	40,4 – 42,6
260 460		M 44	42,6 – 44,2
260 510	R 1 1/2"	M 48	46,0 – 48,6
260 575		M 56	54,0 – 55,8
260 610			56,8 – 58,6

Intended purpose

Universal stoppers series 260

For internal threads and drills

Item number	For internal threads Size DIN 13		For internal threads Size DIN 2999	For smooth drill of Ø ... to Ø ...
260 095			M 10 x 1 / M 10 x 0,75	9,0 – 9,7
260 125	R ¼"		M 14	11,5 – 11,9
260 140			M 16	13,4 – 14,2
260 155	R 3/8"		M 18 / M 16 x 1	14,7 – 15,4
260 160			M 18	15,3 – 16,3
260 185	R ½"		M 20 x 1,5	17,8 – 18,8
260 190	R ½"		M 20	17,0 – 19,7
260 200			M 22	19,0 – 19,7
260 205	R ½"		M 22	19,0 – 21,7
260 210			M 24	20,3 – 21,4
260 225				21,4 – 22,1
260 245	R ¾"		M 27	23,5 – 24,3
260 285				27,5 – 28,6
260 310	R 1"			30,0 – 30,7
260 350				34,0 – 34,8
260 375			M 42	36,5 – 37,6
260 400	R 1 ¼"			38,8 – 40,3
260 440			M 48	42,8 – 43,8
260 460	R 1 ½"			45,0 – 46,3
260 510			M 56	50,0 – 50,8
260 575	R 2"		M 64	56,5 – 57,9
260 610				59,5 – 61,2